

Camera Link Frame Grabber

Specifications

Model	PCIe	Interface	Camera Number (Max)	Data Speed (Max)	Power
Vulcan-sCL PE4 DBase	PCIe2.0×4	2×Base, SDR	2	6.8Gbps	<8.5W
Vulcan-sCL PE4 Full	PCIe2.0×4	2×Full, SDR	2	6.8Gbps	<8.5W

CoaXPress Frame Grabber

Specifications

Model	PCIe	Interface	Camera Number (Max)	Data Speed (Max)	Power
Vulcan-CXP6-2	PCIeGen3x4	2×CXP6, DIN 1.0/2.3	2	12.5Gbps	<11.0W
Vulcan-CXP6	PCIeGen3x4	4×CXP6, DIN 1.0/2.3	4	25.0Gbps	<16.0W
Vulcan-CXP6-8	PCIeGen3x8	8×CXP6, DIN 1.0/2.3	8	50.0Gbps	<18.0W
Vulcan-CXP12-1	PCIeGen3x4	1×CXP12, Micro BNC	1	12.5Gbps	<11.5W
Vulcan-CXP12-2	PCIeGen3x4	2×CXP12, Micro BNC	2	25.0Gbps	<13.0W
Vulcan-CXP12	PCIeGen3x8	4×CXP12, Micro BNC	4	50.0Gbps	<17.5W

10 GigE Vision Frame Grabber

Specifications

Model	PCIe	Interface	Camera Number (Max)	Data Speed (Max)	Power
Vulcan-EXGV-S-2	PCIeGen3x4	2×10G, RJ45	2	20.0Gbps	<15.6W
Vulcan-FXGV-S-2	PCIeGen3x4	2×10G, SPF+	2	20.0Gbps	<15.6W
Vulcan-EXGV-S-4	PCIeGen3x4	4×10G, RJ45	4	40.0Gbps	<13.5W
Vulcan-FXGV-S-4	PCIeGen3x4	4×10G, SPF+	4	40.0Gbps	<13.5W

10GigE NIC

Specifications

Model	PCIe	Interface	Camera Number (Max)	Data Speed (Max)	Power
Cannon-EXGV-S-1A	PCIeGen3x4	1×10G, RJ45	1	10.0Gbps	<4.75W
Cannon-EXGV-S-2A	PCIeGen3x4	2×10G, RJ45	2	10.0Gbps	<11.3W
Cannon-EXGV-S-1B	PCIeGen2x4	1×10G, RJ45	1	10.0Gbps	<6.1W